

UPS2000-G Series

(1-3kVA)

Introduction

UPS2000-G series with a capacity ranging from 1kVA to 3kVA is an online double conversion power system that delivers continuous, high-quality AC Power. It's really a perfect power protection solution for small power scenarios. It's support tower and rack installation.

Scenarios

- Small and medium-sized enterprises, large enterprise branch offices, bank branches and other small data centers
- Networks, communications systems, automatic control systems and other precision equipment

Features

Reliable

- Wide input voltage range to minimize battery use
- Online double conversion power system provides continuous, high-quality AC Power

Efficient

- Efficiency up to 90%, reduce energy consumption, green and energy-saving
- Ultra small volume, compared to the traditional UPS system to save space

Simple

- LCD screen supports real-time monitoring and convenient operation
- Built-in battery, easy to use
- Enables quick and easy configuration of the UPS
- NetEco network manager, supporting centralized management to all the UPSs



UPS2000-G-1K/2K/3K

Specifications

Rated capacity (kVA/kW)		1kVA/0.8kW	2kVA/1.6kW	3kVA/2.4kW	
Input: Output		1-in: 1-out			
Mains Input	Input Wiring	L+N+PE			
	Rated Voltage	200/208/220/230/240VAC			
	Input Voltage Range	110-300VAC			
	Input Frequency Range	40-70Hz			
	Input Power Factor	0.99			
Bypass Input	Input Rated Voltage	200/208/220/230/240VAC			
	Input Frequency Range	50/60±3Hz			
Battery	Battery Voltage	Standard	24VDC	48VDC	72VDC
		Long Backup	36VDC	72VDC	96VDC
Output	Output Wiring	L+N+PE			
	Output Connections	4 X IEC C13	6 X IEC C13	6 X IEC C13 + 1 X IEC C19	
	Rated Voltage	200/208/220/230/240VAC ±1%			
	Output Frequency	Tracking the bypass input (Normal mode); 50/60Hz ± 0.05%			
	Output Power Factor	0.8			
	Waveform	Sinewave, THDv< 3%			
	System Efficiency	88%	89%	90%	
Environment	Operating Temperature	0 to 40°C			
	Storage Temperature	-40 to +70°C (battery: -20 to +40°C)			
	Relative Humidity	0%–95% RH (no condensation)			
	Operating Altitude	0-1000m. Above 1000m, derating rate based on EN/IEC 62040-3			
	Audible Noise	<50dB			
Others	D x W x H (mm)	Standard	88 × 438 × 310	88 × 438 × 410	88 × 438 × 630
		Long Backup	88 × 438 × 310	88 × 438 × 410	88 × 438 × 410
	Weight (kg)	Standard	11.1	18.8	28.9
		Long Backup	6.0	8.7	9.3
	Certifications	EN/IEC 62040-1; EN/IEC 62040-2; EN/IEC 62040-3; CE; CB; RoHS, REACH, WEEE, etc.			
	Communications	USB&RS232(optional RS485/Dry contact/SNMP)			

Notice:

1. The UPS series are for commercial/industrial use and not used for life support equipment;
2. The critical systems concerning economic and public security must adopt power supply architecture that comply with Uptime TIER III or TIER IV requirements stated in TIA942.

Copyright © Huawei Technologies Co., Ltd. 2018. All rights reserved.

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

General Disclaimer

The information in this document may contain predictive statements including, without limitation, statements regarding the future financial and operating results, future product portfolio, new technology, etc. There are a number of factors that could cause actual results and developments to differ materially from those expressed or implied in the predictive statements. Therefore, such information is provided for reference purpose only and constitutes neither an offer nor an acceptance. Huawei may change the information at any time without notice.

HUAWEI TECHNOLOGIES CO., LTD.

Huawei Industrial Base
Bantian Longgang
Shenzhen 518129, P.R. China
Tel: +86-755-28780808

www.huawei.com